

690-3800MHz Power Splitter 2/3/4 way 4.3-10 Female

- Wide frequency range 690 to 3800 MHz for 2G/3G/4G/LTE/5G applications
- Low passive intermodulation 160dBc
- Low VSWR & insertion loss
- Indoor & outdoor use; IP65
- Connector Type N, 7/16 DIN or 4.3/10 Available

Specifications :

Part No.	HT-PS02-638-160-43F	HT-PS03-638-160-43F	HT-PS04-638-160-43F
Electrical			
Frequency range (MHz)	690-3800		
VSWR	≤1.25		
Insertion Loss(dB)	≅ 3.0±0.4	≅ 4.8±0.5	≅ 6.0±0.6
Intermodulation (dBc)	≤-160dBc (with 2×43dBm)		
Impedance (Ω)	50 Ω		
Input power (W)	300		
Environmental			
Operation temperature	-40 °C to +65 °C		
Storage temperature	-55 °C to +85 °C		
Relative humidity	5% - 95%		
Application	Indoor or outdoor (IP65)		
Mechanical			
Connector	4.3-10-Female		
Color	Black or customized based on requirements		
Weight(kg)	0.20	0.30	0.40
Dimension(mm)	157 x 25 x 25	188 x 25 x 25	188 x 25 x 25

Product Image:



Outline drawing :

